## PATENT SPECIFICATION



Date of Application and filing Complete Specification Aug. 30, 1951. No. 20533/51.

Complete Specification Published April 1, 1953.

Index at acceptance :- Class 80(iv), L.

## COMPLETE SPECIFICATION

## Covers for the Rims of Steering and the like Wheels

I, ADTHORY CESARD ANSELDY, (known as Anthony Cesar Anselm), a British Sub-ject, of Silmay Works, King's Road, New Haw, Addlestone Weybridge, Surrey, do haw, Addlestone Weybridge, Surrey, do
bereby declare the invention, for which I
pray that a patent may be granted to me,
and the method by which it is to be performed, to be particularly described in
and by the following statement:—

This invention relates to covers for the
rims of steering and the like wheels, and
has for an object the provision of an
improved form of such covers.

Steering wheels are known in which the

Stearing wheels are known in which the 15 rim has a cover of elastic material which fits singly around the rim without the necessity for any fastening devices and has a roughened or corrugated outer surface which increases the security of the 20 grip necessary for steering a vehicle such as a motor car.

as a motor car.

According to the present invention there is provided for a steering or like wheel an independent cover of elastic 25 material of substantially U section which is sprung over the rim of the wheel so as to adhere tightly thereto, and has an outer surface formed as ribs substantially parallel to one another and to the axis of the wheel. Preferably the circumferential edges of the cover are formed as beads.

The clastic material may be one of the well known plasticised synthetic resins, and the cover may be formed by extrusion as and the sade of a suitable length of the extruded material joined securely, for example by heat welding the joint.

If desired the plasticised cover may be toughened by treating the extruded material of which it is made with a solvent for the pasticiser, either before or

vent for the pasticiser, either before or efter the cover is fitted to the wheal.

In the latter case the cover in its flexible state may be fitted to the wheel rim and subsequently shrunk down hard on the rim by scaking the latter, with the cover in place, in solvents which extract the plasticiser and render the cover hard,

[Price 2/8] 45 C

tough and difficult to remove from the

One way of carrying the invention into effect will now be described by way of example end with reference to the accompanying drawing in which:

Figure 1 is a plan view of a motor car 55 sterring wheel with cover attached.

Figure 2 is a varied section of the ripe

steering wheal with cover attached.

Figure 2 is a radial section of the rim of the wheel of Figure 1.

Figure 3 is an enlarged view of part of Figure 1, partly in aaction.

Reterring to the drawings, a cover 1 of plasticised synthetic resin with its ribbed outer surface 2 and beaded edges 3 is formed by axtrusion and the ends of a piece of the correct length for the outer curference of the wheel rim 5 are butt walded by heat. The cover is then sprang on to the wheel rim 6 as shown in the drawings. drawings.

To harden and shrink the cover 1 to 70 the wheel rim 5, the covered rim is treated with solvents which extract the plasticisers used in the manufacture of the extrasible naterial.

The invention is applicable to wheels 78 other than motor car steering wheels when a non slipping surface of the wheel rim is

other than motor car steering wheels when a non slipping surface of the wheel rim is desirable, and the cover may be produced in any desired colour or colours.

What I claim is:—

1. A steering or like wheel having an independent cover of elastic material of substantially U section which is epreng over the wheel rim so as to adhere tightly thereto, and has an outer surface formed 85 as ribs substantially parallel to one another and to the axis of the wheel.

2. A steering or like wheel as claimed in

another and to the axis of the wheel.

2. A steering or life wheel as claimed in Chain 1 wherein the cover is formed by extraction of plastic material and the ends 90 of a suitable length of the extruded material are joined scorrely, for example, by heat welding.

3. A steering or like wheel as claimed in Claim 1 or Claim 2 wherein the cover is 95 of plasticised material and when fitted on

٠٠ ٠٠ ١٠٠٠

689,548

.

the wheel rim is treated with solvents to extract the plusticising materials and shrink and harden the cover on the rim.

4. A steering or like wheel substantially as described with reference to the accompanying drawings.

BOULT, WADE & TENNANT, 111 & 112, Hatton Garden, London, E.C.1, Chartered Patent Agents.

Learnington Spa: Printed for Her Mujesty's Stationery Office, by the Courier Press.—1983.

Published at The Patent Office, 25, Southumpton Buildings, London, W.C.2, from which copies may be obtained.

689,548 COMPLETE SPECIFICATION

/ SHEET. This drawing is a reproduction of the Original on a reduced scale.

